




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>G06F 15/00</b>		<b>A1</b>	(11) International Publication Number: <b>WO 00/11561</b>
			(43) International Publication Date: 2 March 2000 (02.03.00)
(21) International Application Number: PCT/US99/19028 (22) International Filing Date: 20 August 1999 (20.08.99) (30) Priority Data: 09/137,618                      21 August 1998 (21.08.98)                      US (71) Applicant: CORPORATE MEDIA PARTNERS doing business as AMERICAST [US/US]; 5th Floor, 3601 W. Olive Avenue, Burbank, CA 91505 (US). (72) Inventor: SEQUEIRA, William, J.; 4248 Balfour Avenue, Oakland, CA 94610 (US). (74) Agent: OSTROW, Seth, H.; Brown Raysman Millstein Felder & Steiner, LLP, 120 West Forty-Fifth Street, New York, NY 10036 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the          claims and to be republished in the event of the receipt of          amendments.</i>	

(54) Title: SYSTEM AND METHOD FOR A MASTER SCHEDULER

## (57) Abstract

A system and method for associating and controlling multimedia supporting events with a primary event. The events are translated into tasks and sent to media servers (130) for execution at a predetermined time by being further translated into media specific tasks to control a bit-pump (150).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## SYSTEM AND METHOD FOR A MASTER SCHEDULER

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

5 This invention relates to a system and method for controlling, identifying and coordinating multimedia assets for a broadcast program and for increasing the tolerance of broadcast systems to the failure of the scheduler.

#### 2. Description of the Related Art

10 The task of producing a broadcast program is a complicated, time consuming and error-prone job. Traditionally, a programmer (which is understood by one skilled in the art to be a person who creates a broadcast schedule, in contrast to a computer programmer who writes code) assigns a broadcast program (a broadcast event), to a time slot and ensures that other events, like interstitial, such as commercials, are available to be inserted into the output stream when a cue tone is detected. If the programmer desires to add other types of  
15 information, such as multimedia data, the programming is complicated even further and may not even be possible using current broadcasting scheduling technology.

There are generally two classes of program schedulers. The first class are traffic system schedulers and these types of schedulers are used primarily in analog and analog-digital hybrid broadcast systems. A common use for this type of scheduler is to sell  
20 advertising space to broadcast sponsors and to control the allocation of ads within a broadcast stream. Generally, program schedulers in this class, use the well-known cue tone method. To schedule a program, a programmer would enter into the scheduler the time when a movie or show was to be broadcast and a list of interstitials that are to be inserted into the movie during the broadcast of the movie. At the appropriate time, the program scheduler itself  
25 would, for example, initiate playing the scheduled movie and prepare the devices, such as tape drives, containing the list of interstitials. Interspersed within the movie are cue tones to indicate where interstitials are to be inserted. A cue tone detector detects the cue tone and inserts an interstitial from the list into the output stream of the movie at each detected cue tone by controlling the device to output the requested interstitial. Ads, treated as interstitial,  
30 are thus merged into a single output broadcast stream.

A second class of program schedulers are broadcast schedulers. These schedulers are used not only to control devices but to also and identify the flow of the various

parts of a broadcast program. An electronic program guide ("EPG") is created from the program schedule data. Broadcast schedulers may interface with other databases, such as system configuration and product databases. In a digital broadcast system (in contrast to an analog broadcast system) the programmer inputs the time that a media bit pump (such as a device to play a DVD movie or even a tape drive) is to play a specific event, where the media resides, what media bit pump should play it and how to control the media bit pump. This information often resides in one or more databases, which can be, for instance, flat-file, relational or object-oriented databases. The typical broadcast scheduler would continuously examine the database and, at the scheduled time, the broadcast scheduler would control the appropriate media server to play the desired broadcast event.

Current broadcast schedulers may be further divided into centralized and distributed architectures. Centralized broadcast schedulers utilizing a centralized architecture are very basic and serve as a repository for data. These types of broadcast schedulers directly control devices such as tape drives and have little or no capability in terms of controlling these devices remotely.

Distributed broadcast schedulers are more sophisticated than centralized broadcast schedulers and may include the ability to control device remotely, that is, the devices and the scheduler do not have to be in the same computer, but may be connected through a network. Although these schedulers often have more sophisticated interfaces to databases than others schedulers, they too can only schedule broadcast events. In operation, when the scheduled time for arrives to broadcast, a movie, for instance, the distributed broadcast scheduler sends out an agent to set-up the movie located on the movie located on the media bit pump and begin playing the movie. Examples of distributed schedulers are systems by SunUp and Lysis.

One major limitation of all these schedulers is that the devices, whether they are bit pumps or analog devices such as tape drives, are unable to operate independently without the scheduler controlling these devices. The scheduler is a single point of failure and in the event of a scheduler failure, the entire broadcast system would fail.

Other limitations of the prior art schedulers include their inability to handle different types of events in addition to simply inserting interstitials. A particular vexing problem is their inability to handle multimedia events. Existing schedulers can deal with a single type of event, but in today's interactive television and digital and multimedia world, it

is desirable to be able to schedule and associate a number of events with a broadcast program. These events may include, for instance, information from an Internet site and supplemental information about the broadcast program itself.

Another limitation is that prior art schedulers are unable to synchronize with  
5 other devices. Yet another limitation is that they can handle only one service model -the traditional broadcast service model with interstitials. Yet further, they cannot integrate new devices and media servers rapidly and easily, do not integrate with content management and do not support last minute schedule changes and transmissions to a set-top box ("STB")

Because of these deficiencies, prior art schedulers are unable to provide the  
10 necessary services required in today's interactive television environment. Accordingly, there is a need in interactive TV to address the deficiencies of prior art schedulers.

### SUMMARY OF THE INVENTION

The present invention solves these deficiencies by providing, in accordance with one aspect of the present invention, supporting events which are associated with primary  
15 events via a graphical user interface. In another aspect of the invention, a distributed broadcast scheduler architecture is disclosed which addresses the deficiencies of prior art program schedulers where devices, such as media servers and tape drives operate independently of the scheduler by being providing, in accordance with one aspect of the invention, a Master Scheduler and a Slave Task Scheduler thereby ensuring that a failure of  
20 the Master Scheduler does not bring down the entire broadcast system. In yet another aspect of the present invention, the Master Scheduler is adapted to schedule *events* where the viewing of an *asset*, such as graphics, animation, audio, text, video, or any other such digital media, constitutes the event and changes to a primary event causes all supporting events to be updated, as necessary.

25 Control of different devices and media servers, and hence, assets, is attained by the use of multiple device independent abstraction layers. In accordance with another aspect of the present invention, the Master Scheduler is a central repository of all schedule data and uses different schedule data models for different media servers.

A programmer enters the programming schedule into the Master Scheduler's  
30 data models. Once entered the Master Scheduler processes the schedule and creates a number of *tasks* based on the schedule. Each task is then distributed to a Slave Task Scheduler on the relevant media server for execution at the proper time. The Slave Task Scheduler is adapted

to track the tasks given to it, and prepare the media device to send the scheduled information at the appropriate time. When the task is completed, the Slave Task Scheduler notifies the Master Scheduler of its completion so the Master Scheduler can track the status of the task and update its database.

5 Another advantage to this architecture over the prior art is the use of heartbeat monitor, which allows the Master Scheduler to determine if the Slave Task Scheduler is "alive" and if not, to institute recovery procedures.

These and additional objects of invention can be obtained by reference to the following detailed description of the preferred embodiments thereof in connection with the  
10 attached drawings.

### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a high-level overview of an exemplary embodiment of a system in accordance with one aspect of the invention.

Figure 2 is a block diagram depicting the compute implementation of the  
15 invention is a system such as that shown in Figure 1.

Figure 3a shows an exemplary embodiment of Service Specific GUI 110.

Figure 3b shows an exemplary embodiment of Master Scheduler 120.

Figure 3c shows an exemplary embodiment of Media Server 130.

Figure 4a and 4b show exemplary embodiments of System Scheduling  
20 Mechanism 340.

Figure 5 shows an exemplary embodiment of Slave Task Scheduler 140.

Figures 6-22 shows exemplary screen shots of one embodiment of Service Specific GUI 110.

Figures 23a, 23b, 24a, 24b, 24c and 24f show exemplary screen shots of  
25 another embodiment of Service Specific GUI 110.

Figures 25-28 shows exemplary data models used on one aspect of the present invention.

Figures 29-31 shows exemplary tables used in Publish and Subscribe 420 and the result of calls to registered routines.

Figures 32a, 32b, 33a and 33b show exemplary embodiments of tables used in  
30 the Queue 3200.

Figure 34 shows one aspect of a finite state machine and four states.

## DETAILED DISCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to Fig. 1, there is shown a system in accordance with one aspect of the invention. In particular, there is shown Service Specific GUI 110 which communicates with Master Scheduler 120 through Service/Master Scheduler API 170. In the preferred embodiment, Service Specific GUI 110 which resides on one computer while Master Scheduler 120 resides on a second computer, thus, Service/Master Scheduler API 170 is comprised of two parts, Service/Master Scheduler API 170a which is part of Service Specific GUI 110 and Service/Master Scheduler API 170b which is part of Master Scheduler 120.

Master Scheduler 120 communicates with Media Server 130 through Master/Slave Scheduler API 180. Media Server 130 is comprised of Slave Task Scheduler 140 which communicates with Master Scheduler 120 through Master/Slave Scheduler API 180 and with Bit Pump 150 through Device Specific API 190. Bit pump 150 controls and retrieves data from Storage Device 160, which may be, for instance, a disk, tape, CD-ROM, DVD, or even a server.

The Master/Slave Scheduler API 180 acts as the interface between Master Scheduler 120 and a media server's Slave Task Scheduler 140. This API is used by Master Scheduler 120, among other things, to distribute, administrate and monitor task and media server availability, heartbeat monitoring, and specific media server control, such as initialization, reset and shutdown. Functions such as heartbeat monitoring, which enables Master Scheduler 120 to ensure that Slave Task Scheduler 140 is alive and operating, allows Master Scheduler 120 to institute a recovery procedure, if necessary.

In the preferred embodiment Master Scheduler 120 communicates with Media Server 130 over a network, and thus Master/Slave Scheduler API 180 is comprised of two parts, Master/Slave Scheduler API 180a and Master/Slave Scheduler API 180b as part of Master Scheduler 120 and Slave Task Scheduler 140, respectively. In another preferred embodiment, Master Scheduler 120 communicates with Media Server 130 using shared memory or a common area of memory. This embodiment allows Master Scheduler 120 to communicate more quickly with Media Server 130 and is also more effective if Master Scheduler 120 and Media Server 130 are in single physical box. Of course, to one skilled in the art, other means of communication may also be used, such as wireless communication techniques.

Slave Task Scheduler 140 can communicate with Bit Pump 150 in a number of different ways, for instance, over a network (LAN, WAN, wired, wireless, optical, RF or otherwise). Since Slave Task Scheduler 140 and Bit Pump 150 may be separate, there is a latency inherent in the system. For example, if Master Scheduler 120 expects Media Server 130 to output a NVOD movie at 8:00 PM, in reality, Slave Task Scheduler 140 must begin sending controls down to Bit Pump 150 at, for instance, 7:59:53 PM. This seven (7) seconds difference, called a delta variable or delta variance, allows time for Slave Task Scheduler 140 to send a command or series of commands over a network to Bit Pump 150 to initialize, retrieve the movie, fill its buffer and begin outputting the requested data by 8:00 PM. Slave Task Scheduler 140 has the appropriate data about the delta variance needed to account for each type of Bit Pump 150 that it may encounter and the interconnections type between it and Bit Pump 150.

In the preferred embodiment, Slave Task Scheduler 140 is incorporated with Bit Pump 150 in one physical case, and thus a traditional network is not needed. Instead, Slave Task Scheduler 140 communicates with Bit Pump 150 using well known techniques of shared memory. This embodiment allows for faster access and reduces the delta variance required for Bit Pump 150 to prepare for and begin retrieving and sending out data.

Device Specific API 190 is comprised of two parts, Device Specific API 190a as part of Slave Task Scheduler 140 and Device Specific API 190b as part of Bit Pump 150.

A programmer uses Service Specific GUI 110 for creating a schedule. Prior to creating a schedule *services* are created. A service is a relationship between a primary event and supporting events. A primary event is an event that a viewer can select from the EPG. A supporting event is an event that is subsidiary to the primary event and provides a viewer with additional multimedia data enhancing the primary event. A *broadcast service* may be defined, for instance, as a primary event with two supporting services - text captions and Internet facts. Once defined, Service Specific GUI 110 is able to use the service definition to constrain the choices made by a programmer to ensure that the desired supporting events are available. For instance, if the primary event is a broadcast show, i.e., a *broadcast event* and the programmer wants, for instance, to provide additional text information about the broadcast event from a data carousel and other facts from the Internet, then there would also be two supporting events - a text caption event and an Internet facts event. Both of these



events are supporting events, while the data carousel and the system which obtains the Internet facts would be the *supporting services*.

5 The relationship between a primary event and a supporting event may be thought of, in graph theory, as an inverted tree where the primary event is a high level node that is visible and selectable by the consumer, while supporting events are either additional nodes or leaves under such node. A service is thus the set of nodes that can be under a particular type of node. Using the above example, for the broadcast service, a broadcast event node can only have a data carousel for text information and/or Internet material for supporting events. The broadcast event node would thus be the root node and, at most, two  
10 leaves (assuming no supporting services for the supporting events) under that root node. If the data carousel is in turn supported by other events, then the data carousel service would not be a leaf, but is itself a node, and would have other leaves under such node.

In the preferred embodiment, the programmer uses a graphical user interface, although other types of interfaces, including non-graphical interfaces, may also be used.  
15 Moreover, Service Specific GUI 110 may be specifically tailored for particular types of program services, such as broadcast, pay-for-view movies, restricted access, public service and children's programming, although one GUI may suffice for all desired services.

Master Scheduler 120 processes the schedule created by the programmer using Service Specific GUI 110 and generates *tasks*. Task are commands which instruct Media  
20 Server 130 to perform an action, such as Initialize or Play. These tasks are then distributed to Slave Task Scheduler 140 in Media Server 130. In accordance with one aspect of the invention, tasks can be distributed months, even years ahead of schedule. Alternatively the tasks can be distributed in "real-time," as long as the distribution is sufficiently prior to the scheduled task to permit Slave Task Scheduler 140 to account for any delta variance.

25 Moreover, in accordance with another aspect of the invention, the distributed nature of the Master Scheduler 120 from the Media Server 130 and the ability to distribute and have tasks executed independently of Master Scheduler 120 provides the benefit of allowing for recovery in the event of a failure in a media server, thereby providing a degree of fault tolerance to system failures. In particular, Master Scheduler 120 monitors the heartbeat  
30 from each media server. The heartbeat is, in its simplest form, a signal from a media server indicating to the Master Scheduler 120 that it is alive and functioning. Master Scheduler 120 can determine from the heartbeat when a media server goes down, and can quickly reassign

tasks to other media servers or backup media servers as necessary. When the media server has been brought back up, its heartbeat will provide an indication of this to Master Scheduler 120, which can then reassign to it any of its original unexpired tasks.

At the appropriate time, Slave Task Scheduler 140 executes the task by issuing a device specific Command or series of device specific commands to Bit Pump 150. Bit Pump 150 responds to the device specific commands by, for example, retrieving the data from Storage Device 160.

Referring now to Fig. 2, there is shown a Computer 210 which executes the code for Service Specific GUI 110. In particular, Computer 210 is, as an exemplary embodiment, comprised of CPU 211 which interacts with Keyboard 212, Monitor 213, Storage 214, Memory 215 and Network Interface 216 and operates in a manner well known to those skilled in art. Although shown in Fig. 2 as a single processor system, Computer 210 is not limited to this embodiment and may be, for instance, a multiprocessor system, mainframe, or even a client/server system. Similarly, Computer 230 and 240 runs the code for Master Scheduler 120 and Slave Task Scheduler 140, respectively. The details of Computer 230 and 240 are likewise well-known to those skilled in the art and may be similar to those computer systems described for Computer 210. Bit Pump 150, upon receipt of device specific command performs the request action, and, if requested to retrieve data, sends that data over Network 270.

In the preferred embodiment, Computer 210 communicates with Computer 230 via Network 220 and Computer 230 communicates with Computer 240 via network 260. As can be appreciated by one skill in the art, Network 220, 260 and 270 do not have to be separate independent networks and may, as an example, be a single network where Computers 210, 230 and 240 are simply nodes on that single network. Network 220, 260 and 270 may, for instance be a LAN, WAN or even a VPN over the Internet and be physically connected or connected wirelessly.

Referring now to Fig. 3a there is shown a more detailed diagram of Service Specific GUI 110. In particular, different supporting services may be addressed and scheduled in different ways. For instance, a data carousel has different specification and information than a NVOD device, which in turn has different specifications than a multiscreen browser service or a music server. Accordingly, different GUIs are available for each of the

different supporting services. These are represented by, but are not limited to, Data Carousel GUI 310a, NVOD GUI 310b, MSB GUI 310c, IPPA GUI 310d and Music GUI 310e.

5 A data carousel media server is a device that provides multiple streams of data, where each stream of data is identified by a process ID ("PID") and where each such stream stores or references data in a number of logical slots. The data carousel then cyclically cycles through the slots for each PID and transmits the data stored or referenced in those slots. A NVOD media server (*Near Video On Demand*) has the ability to retrieve and play a number of different videos on different channels. A MSB media sever (*Multi-Screen Browser*) is a device that is designed to take a number of video streams, for example, a number of broadcast  
10 channels, and display them concurrently on one television screen. The screen may be divided into a number of windows, with each stream displayed in reduced format in a separate window. An IPPA media server (*Internet Push Pull Agent*) is a device that is connected to the Internet and can transmit information from a service such as Pointcast or can retrieve information from an Internet or internal site. A Music media server is a device that transmits  
15 music on one or more channels. These devices are only examples of different types of media servers that may be used in accordance with this invention and there are other types of devices such as channel management devices that may also be used.

Of course, scheduling these different services do not have to be through separate independent GUIs. In the preferred embodiment, these supporting services are  
20 accessible through a single master GUI, with additional details of each supporting service displayed as needed. The user creates the schedule using Service Specific GUI 110, which communicates with Master Scheduler 120 through Service/Master Scheduler API 170a.

Referring now to Fig. 3b, there is shown a more detailed diagram of Master Scheduler 120. In particular, Service Specific GUI 110 communicates with Table  
25 Manipulation Routines 330 to add and manipulate events, as needed, in the relevant data models. More specifically, the data pertaining to events for a particular service, primary or supporting, is stored in as set of tables. The set of tables is called a *data model*, as exemplified by Data Models 320a-e. Each data tables for a particular service model is generally tailored to a specific service, although a single data model may be used for different  
30 services. For example, a data model for a data carousel service may require a specification of the loop cycle of the data carousel, number of slots and data storage size of slots. In such a case Data Carousel Data Model 320 may include data pertaining to the loop cycle of the data

carousel, slots, data storage size of each slot and the data model may hold data and packet information. Of course, other information may be required or included in the tablets, as determined by the needs of the service. In the preferred embodiment, the data models are object-based and an object-oriented database is used.

5 As an exemplary embodiment, there is shown Data Carousel Data Model 320a, NVOD Data Model 320b, MSB Data Model 320c, IPPA Data Model 320d and Music Data Model 320e, which correspond to different supporting services scheduled using Data Carousel GUI 310a, NVOD GUI 310b, MSB GUI 310c, IPPA GUI 310d and Music GUI 310e, respectively. It is not required, however, that each service has its own data model. In some instances where the services are similar, a single data model may be used for a number of different services.

Table Manipulation Routines 330 provide a means for Service Specific GUI 110 and other processes, such as System Scheduling Mechanisms 340, to create, store, retrieve and remove event data from the Data Models 320a-e (and any other data models). Usually there are different routines for different Data Models since the data tables tend to be different for each service and hence data model. In the preferred embodiment additional routines may be designed, constructed and added to Table Manipulation Routines 330 to provide increased flexibility and expandability in the system. Alternatively, the different routines may be simplified and abstracted at higher levels to provide a set of generic APIs to include in the Service/Master Scheduler API 170 to minimize the need to construct new and different routines for Table Manipulation Routines 330 for each Service Specific GUI 110.

Table 1, below, shows exemplary Table Manipulation Routines in the preferred embodiment which may be used to manipulate various data models.

**Table 1**

Routine	Type	Comment
Tmr_CreateDM	Generic	Creates an instance of a data model
Tmr_DefineDMTables	Generic	Defines the set of tables of the data model
Tmr_DefineTableField	Generic	Adds a field to a table definition
Tmr_CreateTableEntryInstance	Generic and/or Specific	Populates an entry into a data model table.
Tmr_ImportDMData	Generic	Imports data from an external data model
Tmr_ExportDMData	Generic	Exports data model local data
Tmr_DefinesSched	Generic	Schedule data may be spread across several tables. This routine creates a <i>virtual</i> schedule table. Note: It is possible to have different types of schedules within the same data model

Routine	Type	Comment
		by defining different schedule tables. *
Tmr_DefineSchedField	Generic	Defines a field to be added to a virtual schedule table.
Tmr_CreateSchedInstance	Specific	Populates an instance of a schedule table. This routine is specific to a data model.
Tmr_TransSchedToTask	Specific	Translate an instantiated and populated schedule into a task.
Tmr_DistributeTask	Generic	Distributes a task to a specific Task Scheduler or Media Server
Tmr_MonitorSched	Generic	Reports on the status of a particular schedule
Tmr_SetTimer	Generic	Sets a timer trigger
Tmr_RemoveTimer	Generic	Removes a timer trigger
Tmr_RegisterEvent	Generic	Creates a new event
Tmr_RegisterEventInterest	Generic	Registers interest in a specific event.
Tmr_LogEvent	Generic	Logs the occurrence of a specific event.

The routines shown in Table 1 are not exhaustive and other routines not shown may be added such as routines for the deletion of schedule instances, removal of fields in the tables of a data model, etc. These Table Manipulation Routines may search for data using SQL (Structured Query Language) search procedure or any other form of database control command to control a database, such as an object-oriented or relational database engine.

Scheduling System Mechanisms 340 are routines/mechanisms common to the scheduling of events task and accesses the data models by Table Manipulation Routines 330. Exemplary mechanisms may include, timers, event publishers and subscriber interfaces, distribution of tasks (which in the preferred embodiment does not transform a task into a schedule). Scheduling System Mechanisms 340 also perform the function of generating tasks from a schedule. These tasks are then distributed to Slave Task Scheduler 140 through Master/Slave Scheduler API 180.

Referring now to Fig. 3c there is shown a more detailed diagram of Media Server 130. Specifically, there is shown a number of Media Servers 130a-e. Media Servers 130 a-e are comprised of Master/Slave Scheduler API 180b, Task Schedulers 140a-e, Device Specific APIs 192a-e, Bit Pumps 150a-e and Storage Devices 160a-e, respectively. Using Media Server 130a as an exemplary illustration, Data Carousel Task Scheduler 140a receives a task from Master Scheduler 120 via Master/Slave Scheduler API 180b. At the appropriate time, Data Carousel 140a processes the task into device specific commands, in this example, data carousel commands and sends those commands via Data Carousel API 192a to Data Carousel Bit Pump 150a, which performs the requested commands and, if necessary, interacts

with Storage Device 160a. The other Media Servers 130b-e generally operate in a similar manner.

Referring now to Fig. 4a there is shown a more detailed diagram of System Scheduling Mechanisms 340 for one embodiment. In particular, there is shown Task Distributor 410 which communicates with Table Manipulation Routines 330, Event Publish and Subscribe 420 and Thread Pool and Queue 430. Event Publish and Subscribe 420 provides a mechanism to update the data models and communicates with Thread Pool and Queue 430, which in turn also communicates with Master/Slave Scheduler API 180a, Timers 440 and Other Events 450.

In operation, Thread Pool and Queue 430 and Event Publish and Subscribe 420 form the core of Scheduling System Mechanism 340. Threads are used by different parts of the system to perform various computations, functions and tracking. For instance, once a schedule is created, Task Distributor 410 transforms the schedule into a series of tasks and assigns the task to a thread and places the thread in Thread Pool and Queue 430. At the appropriate time, the thread may issue a command via the Master/Slave Scheduler API 180a to Media Server 130 using some network communication mechanism. In the preferred embodiment, that communication mechanism is CORBA, although other methods, such as a remote procedure call ("RPC") may be used. The thread then blocks, waiting for a response. Upon receipt of the response, the original thread unblocks and returns control to the caller, in this case the Thread Pool and Queue 430.

In the case of the receipt of a message from, for instance, a media server, expiration of a timer, or other platform event, the thread is allocated and carries the event notification into a queue in Thread Pool and Queue 430. For example, the notification of a task transitioning from "installed" to "executing" status is captured and transported by the thread to a predetermined queue. As soon as the notification is dropped into the queue, the thread returns a message to the original sender indicating the status of the requested operation.

The publish and subscribe mechanism of Event Publish and Subscribe 420 allows routines to register interest in a particular event, causing the routine to be notified when the event has arrived. Using a publish and subscribe mechanism thus allows for specific and selective propagation of information to supporting events when the primary event has changed. In one embodiment, the primary events are published, that is registered so that the

system can keep track of those events that may affect other events. A consequent change causes the subscribing mechanism to determine what events are to be modified and what procedures to use in such modification. The result is that changing one event can easily propagate changes and updates to other related events.

5                   Figure 4b discloses a second, and preferred, embodiment where Thread Pool and Queue 430 is an integral part of Event Publish and Subscribe 420. In this embodiment, events are registered in the Thread Pool and Queue 430 through Event Publish and Subscribe 420. Preferably, all events are registered to provide a means for tracking the status of tasks. For instance, when a task has successfully executed, a message may be sent to Event Publish  
10                   and Subscribe 420 to execute certain routines based on the receipt of that message.

                  In accordance with one aspect of the present invention, Master/Slave Scheduler API 130 allows Master Scheduler 120 to deal only with the issues of scheduling and the translation of schedules into tasks without having to account for media server specific issues, unlike prior art schedulers. In the preferred embodiment, the Master/Slave Scheduler  
15                   API 130 is a synchronous protocol for distributing to and managing tasks in remote media servers. The protocol is synchronous (i.e., the blocking of API calls is allowed as long as it is coupled with a time-out and reissue protocol policy) because it is expected that network traffic is low and that inherent latencies are tolerable. Table 2 sets forth one embodiment of the Master/Slave Scheduler API 130.

20                   It is assumed in the preferred embodiment that CORBA's IIOP is used for the passing of messages, but is not limited to the use of IIOP. Other protocols may of course be used, such as TCP/IP, and the selection of such other protocols is not important to practicing this invention. In addition, all events within a Master Scheduler should be unique and identified by a MasterId. This permits Multiple Master Schedulers, each with its own  
25                   identifier, to co-exist as long as each event is uniquely identified by a combination of its MasterId and EventId. Multiple Master Scheduler may take the form, for instance of, of having east and west coast Master Schedulers, each with its own local scheduler, but together there is a single, albeit distributed, schedule. Tasks should also carry the same Id from which it was derived (and likewise, the same unique combination of Master Scheduler Id and  
30                   EventId if multiple Master Scheduler's are used). In the preferred embodiment tasks have the form of a tuple *[taskId, assetList, operator, time, data]*. *AssetList* is a list of assets over which the operation identified by *operator* is performed at the *time*. *Data* is used for data

used to support *operator*. As previously discussed, a synchronous protocol with a blocking RPC mechanism is preferred, although other synchronous protocols may be used. For simplicity, if a schedule's time has expired, the preferred embodiment automatically deletes that schedule.

5

**Table 2**

Message	Function	Fields	Return Value	Comments
Ms_InstallTask	Installs a task in a slave scheduler	IN: MasterId SlaveId TaskId < notifySw > {taskData}	msSUCCEED msFAIL	The <b>notifySw</b> [on, off] indicates whether the slave should notify the status of the task whenever it changes state. Specific task data is transported by <b>taskData</b> and will vary depending on the type of task. E.g. time, date, asset list, operation, stream number. <b>Note:</b> Tasks that have expired (i.e. their execution time is past the current time) can not be installed.
Ms_ModifyTask	Modifies the data of a task installed in a slave scheduler	IN: MasterId SlaveId TaskId {IschedData}	msSUCCEED msFAIL	Specific task data is transported by <b>taskData</b> and will vary depending on the type of schedule. E.g. time, date, asset list, operation, stream number. It will replace the pre-existent task data.
Ms_RemoveTask	Removes a task from a slave scheduler	IN: masterId slaveId taskId	msSUCCEED msFAIL	Removes <b>taskId</b> from the slave scheduler timeline. If the task has expired in the slave it is automatically removed.
Ms_TaskImage	Retrieves a list of tasks installed in a media server	IN: masterId slaveId {taskIdList} OUT: {tasks}	msSUCCEED msFAIL	Retrieves a set of tasks from a task scheduler, including all the supporting data. Hence, <b>{tasks}</b> is composed of tuples of the form [taskId, assetList, operator, time, data].
Ms_MonitorTask	Monitor the status of a task	IN: masterId	msSUCCEED msFAIL	This message instructs the slave to send a



Message	Function	Fields	Return Value	Comments
	executed by a slave scheduler	slaveId taskId < monitorSw >		notification every time the state of <b>taskId</b> changes. E.g. when the task is inactive and changes to executing, when it finishes, if an when it encounters and error condition, etc. The <b>monitorSw</b> [on, off] turns monitoring on or off.
Ms_MonitorSlave	Monitor the status of a particular slave scheduler	IN: masterId slaveId secs < monitorSw >	msSUCCEED msFAIL	Used to set a heartbeat every secs of time, to guarantee the sanity of a slave scheduler. The <b>monitorSw</b> [on, off] turns monitoring on or off.
Ss_TaskStatus	Notifies the Master Scheduler about a change in the status of a task	IN: masterId slaveId taskId < taskStatus > lstatusData	msSUCCEED msFAIL	The new state of the schedule is sent via <b>taskStatus</b> [installed, waiting, executing, (completed, removed), error1,... , errorN], which indicates the new state just entered. The field <b>statusData</b> holds data resulting from the change of state of the schedule. E.g. a call collector returning billing information as a consequence of the completion of a call task.
Ss_HeartBeat	Notifies the Master that the slave scheduler is alive and well	IN: slaveId masterID < slaveStatus >	msSUCCEED msFAIL	The heartbeat message is sent every time period to the master, with a <b>slaveStatus</b> [normal, alarm1,... , alarmN]. Note: The heartbeat is really a cross-tier function and should be an SNMP level service.
Ss_TaskChange	Notifies the Master Scheduler about a change in the task data	IN: slaveId masterId taskId (taskData)	msSUCCEED msFAIL	Schedule data may be changed manually, which would create and inconsistency between the slave and the master. This message notifies the master that synchronization of the master and slave data is required, with <b>taskData</b>

Message	Function	Fields	Return Value	Comments
				being the current data.
Ms_SyncSlaveClock	Synchronizes the slave scheduler clock with the Master Scheduler clock	IN: masterId slaveId syncTime	msSUCCEED msFAIL	The syncTime is a structure composed of the <b>timeZone</b> , <b>date</b> and <b>time</b> , the latter expressed in seconds. The <b>timeZone</b> [GMT0, ....., GMTNJ is used for locality. It is used to synchronize the clocks of the slaves with the master scheduler clock. <b>Note:</b> This is a soft clock sync function. A hardware clock sync is highly recommended as there is some inherent clock drift in this approach.
Ss_GetMasterClock	Get a clock value from the Master Scheduler to synchronize the local slave clock	IN: slaveId masterId OUT: syncTime	msSUCCEED msFAIL	Returns a <b>syncTime</b> structure containing the current master clock time.  <b>Note:</b> This is a soft clock sync function. A hardware clock sync is highly recommended as there is some inherent clock drift in this approach.
Ms_ControlSlave	Issues a control instruction specific to a slave device	slaveId masterId {slaveControl}	msSUCCEED msFAIL	Control of specific features of slave devices may demand control calls that are specific to the slave device. E.g. a NVOD server may require an emergency procedure to restart the system or change output ports for a stream. A series of <b>Ms_ControlSlave</b> messages containing <b>slaveControl</b> instructions (specific to a slave device) can achieve such specific need. <b>Note:</b> This API message is used to code emergency procedures and specific setup and teardown procedures (such as initialization)

Message	Function	Fields	Return Value	Comments
				for the specific devices.
<ul style="list-style-type: none"> <li>• {and} denote a list of items.</li> <li>• &lt; and &gt; denote an enumerated set of values.</li> <li>• The suffix Sw denotes a variable used as a switch with values {on, off}.</li> <li>• * Ids are 64-bit integers.</li> <li>• A prefix of Ms (for Master Scheduler) indicates messages flowing from the Master Scheduler towards a Slave Task Scheduler.</li> <li>• A prefix of Ss (for Slave Scheduler) indicates messages flowing from the Slave Task Scheduler to the Master Scheduler.</li> </ul>				

Referring now to Fig. 5, there is shown a more detailed diagram of Slave Task Scheduler 140. Specifically, Master/Slave Scheduler API 180b denotes that portion of the Master/Slave Scheduler API 130 that resided in Slave Task Scheduler 135. It sends and receives Master/Slave Scheduler API 130a messages and passes those message to Timeline and Task Management 510. Timeline and Task Management 510 process the messages, manipulates the timeline, and where appropriate, executes the task by sending the task to Task Translation Layer 520. Translation Layer 520 translates the task into a form to send to Bit Pump 150 via Device Specific API 190a. In the preferred embodiment Master/Slave Scheduler API 180 and Timeline and Task Management 510 are device independent while Task Translation 520 and Device Specific API 190 are device dependent.

In the preferred embodiment, Task Translation Layer 520 communicates with Timeline and Task Management 510 via Task Translation API 515, shown in Table 3.

**Table 3**

MESSAGE	FUNCTION	FIELDS	RETURN VALUE	COMMENTS
Tt_TaskInit	Initialize the Task Translation Layer and the device	OUT: OpStatus	TtSUCCEED TtFAIL	Initializes Task Translation Layer 420 and the Media Server controlled by it. OpStatus conveys the result of the initialization procedure.
Tt-Task	Execute a task	IN: TaskId < asset_list > Operator < op_spec_data > OUT: OpStatus	TtSUCCEED TtFAIL	taskId identifies a task that is to be executed immediately. < asset_list > denotes a list of physical names. In the NVOD server case, < asset list > is equivalent to play list.

MESSAGE	FUNCTION	FIELDS	RETURN VALUE	COMMENTS
				<op - spec_data > is a variable length list used to transport device dependent information necessary to carry out the operation. The valid values for operator are (in the NVOD server case): ttPLAY, ttPAUSE, ttABORT.
Ms_TaskStatus	Callback returning a task status	IN: TaskId Status StatusText OUT: OpStatus	TtSUCCEED TtFAIL	status has one of the following values: ttLOADED, ttEXECUTING, ttCOMPLETED, ttERROR. StatusText is used to further specify the nature of error.

For every task to be executed, Task Translation Layer 520 creates an instance of a finite state machine (FSM) to track the state transitions of the task as it is carried out to completion by the media server. The FSM instance is identified by the taskId of the task being tracked.

5           The state set of a FSM instance contains at least one state for each status value. Generic states for all media servers include states for ttLOADED, ttEXECUTING, ttCOMPLETED, and ttERROR. Take for instance, an Associated Press video server. The status ttLOADED from the video media server indicates that the task is loaded, queued and awaiting executing. If offline, then an error message, ttERROR, is generated with the specifics of the error in the payload and sent back to Master Scheduler 120.

10           Of course, other states and status may be used. Another embodiment is also shown in Figure 34. For example, a FSM to track the status of a NVOD server operation has the status value states and may have others to account for intermediate operations such as:

- 15
- Opening a session
  - Opening a stream
  - Playing a stream
  - Closing the stream
  - Closing the session

20           Tuple operators for other types of media servers, which in turn may be translated into device specific API calls, are as follows:

- Data Carousel: ttINTERLEAVE, ttNEW\_DELIVERY\_LIST, ttSTART  
ttSTOP, ttREMOVE
- MSB: ttNEW\_CHANNEL-\_LINEUP, ttSTART, ttSTOP

Reference is now made to Fig. 6 which shows exemplary screen shots of Service Specific GUI 110. In particular, there is shown Screen 600 which consists of Control Buttons 610a, 610b, 610c and 610d. These Control Button allow a user to control various functions of the exemplary system. Screen 600 is further comprised of Schedule Array 620 arranged as a series of Time Columns 630a-630d and a series of Program Rows 640a-640i. Time Columns 630 represent one hour intervals in this example and Program Rows 640 represent the program listings for a number of channels. The intersection of the Time Columns 630 and Program Rows 640 comprise Cells 622 in Schedule Array 620. Although the cells shown are in equal time intervals, other ways may be shown for unequal time intervals. For instance, to indicate a two-hour show, a cell spanning the length of two one-hour cells, representing a two hour time interval may be used. In another embodiment, each cell may be the same, but the second cell in a two-hour time interval may be a different color to indicate that that time slot is unavailable. In the preferred embodiment the time interval displayed may be modified to suit the users needs, such as by one-half hour intervals rather than by one hour intervals and the way varying time slots are shown may also be selected and modified.

Fig. 7 show an exemplary dialog box when Control Button 610d is selected. Dialog Box 700 allows the user to enter a date that the user would like to view the schedule from. In this example, the user has entered August 26, 1997 and 12:00PM.

Fig. 8 shows an example of the results of selecting Control Button 610d where the date of August 26, 1997, and the start time of 12:00AM has been entered. In particular Cells 622a-d show four primary events scheduled. Cell 622a shows that a multi-screen browser channel, MSB-101, has scheduled at 1:00pm the primary event, and that the location of where to obtain the event is detailed in a file called "config1. dat." Cell 622b shows a second multi-screen browser channel, MSB- 102, has scheduled at 12:00pm primary event, and that the location of where to obtain the event is detailed in a file called "config2. dat." Cell 622c indicates that an Internet channel, INET-101, is to display at 2:00pm, and that the information, such as the web site URL, is identified in the data from the listed file. Cell 622d

shows a standard broadcast channel, KABC, has a sports event scheduled for 12:00pm. and that the event is a TV event, with a program name ESPY. In Fig. 8, Cell 622a is selected.

Fig. 9 shows the screen shot of Fig. 8 with Cell 622c selected. When selected, the full name of the primary event is shown, in this example, the web site URL is identified in the data from the data file "stocks.sdf."

Figure 10 shows Cell 622d selected. The information is displayed as Primary Event 1001 and the triangle icon on the left of the indicates that there are one or more supporting events below it that can be selected. This format is also shown in Figures 8 and 9 in cells 622a and 622c, respectively.

Figure 11 depicts Cell 622d with Primary Event 1001 showing Supporting Event 1101. Supporting Event 1101 is displayed by the user clicking on the triangle icon in the left side of Primary Event 1001. As can be seen, this triangle icon as changed to a downward pointing triangle to indicate that other supporting events are being displayed. Supporting Event 1101 refers to the information in a file identified as " sworks. 2mt ", which is located in a data carousel slot. As can be seen, Supporting Event 110 also has a right pointing triangle indicating that other events subsidiary to this event. An additional aspect of the display of Supporting Event 1101 is that the supporting event is displayed in a hierarchical fashion, thereby showing the relationship between the primary event and supporting event. This also depicts the relationship of supporting events to primary events in a graph. The invention is not limited to showing the hierarchical structure shown in this embodiment and other methods are known to one skilled in the art.

Figure 12 depicts Menu 1201 which is displayed upon selecting Supporting Event 1101. This menu has menu items which allow the user to Add and Insert additional supporting events, as may be needed for Supporting Event 1101 as a hierarchical structure. The Add menu item is used to append to the list a new supporting event. The Insert menu item is used to insert a new supporting event in the list between two existing supporting events. Also shown are the menu items to Open a service, show the Details of a selected service or Remove the associated service for the primary event. In this figure, the Details menu item is highlighted.

Figure 13 shows the results of selecting the Details menu selection from Menu 1201 for Supporting Event 1101. In particular, Dialog Box 1301 is showing further detailed information pertaining to Supporting Event 1101. The information shown is that the

Supporting Event 1101 is scheduled for August 26, 1997 (Field 1302) at 12:00 (Field 1303) for one hour, stopping at 1:00 (Field 1305) and for one day only (Field 1304). Of course, other information may be shown depending on the level of information desired. Thus, Dialog Box 1301 in an alternative embodiment may display, for instance, information about the location of files relating to that event.

Referring now to Figure 14, Cell 622a shows Primary Event 1401, which details are located in a file "config1.dat." By selecting ControlButton 610c in Figure 15, Menu 1501 is displayed. When the Display Times menu item is selected, the time duration is displayed for all selected events. For example, Figure 16 now shows that Primary Event 1401 has the display times shown as part of its information, in contrast to that shown in Figure 14. In this example, scheduled time for this Primary Event is one and one-half hour, from 1:00 to 2:30, which is not obvious from the display grid alone. Of course, other ways of indicating such times may be used. One way would be to size Cell 622a so that it is proportional to the duration of the event. In this example, the Cell 622a would then extend from 1:00 to the midway through column 630d. Another way would be to use different colors for each different duration, such as white for half-hour intervals, blue for one-hour intervals. Yet other ways would be different combinations of these ways to display time. Still further, a grid could be used with channels heading the columns and time identifying the rows. Another way would be to display the information in a list format. Other ways would be apparent to those skilled in the art and the specific embodiments shown here are not intended to limit the scope of the invention.

In Figure 17, Menu Item 1601a is selected, the result which is shown in Figure 18. In particular, Figure 18 shows an exemplary simplified EPG database, that is, the database for the primary events. Each event is stored as a record, shown here are Records 1820a and 1820b. Each record is comprised of a number of fields, shown here as Fields (or, in the case of a table, viewed as columns) 1810-1816. ServiceID Field 1810 stores a logical identifier for a service. In the preferred embodiment, the ServiceID is mapped to a channel in a Nagra system. Provider ID Field 1811 indicate the provider of the data. Shown here, Court is the data feed provider for a Court TV channel and KABC-ABC is the provider for the KABC broadcast. Fields 1813-1816 show the times of the services listed provided to the EPG. An alternate view would display some or all supporting events and other pertinent information for each service and event thereby providing a user with varying levels of detail.

Figure 19 depicts a more detailed editing/display screen for a record in the EPG database. In particular, Program Title Field 1910 holds the name of the program, "ESPY" in this example. ProgramID Field 1911 holds a logical identifier for the ESPY program. Type Field 1912 holds data indicating the type of program, which in this case is a standard television program - type TV. Other types may include, for example, NVOD and INET. PPV Field 1913 indicates whether the program is a pay-per-view program or not.

Figure 20 depicts an editing/display screen for the GDC database. In particular, AssetURL Field 2010 holds the location for a specific asset for the generic data carousel. SpoolID 2010 holds the logical identifier for a specific spool for a data carousel, that is, a logical grouping of files that may or may not be stored together physically. Bandwidth Field 2012 indicates the bandwidth of the spool. The data in QueueSlot Field 2013 allows the data carousel to assign different priority levels to different assets, thereby affecting the level of responsiveness - which in turn affects the delta variance.

Figure 21 depicts an editing/display screen for a MSB (Multi-Screen Browser) database records. A multi-screen browser service combines a number of channels onto one screen. Using this technique, the MSB service can show several programs at one time on a television screen where each program is displayed in a reduced format. CombinerID Field 2110 identifies the combiner, a device for integrating multiple channels into one view, for the programs identified in Program ID Field 1911 for the particular combiner.

Figure 22 depicts an editing/display screen for the INET (Internet channel) database records. ServiceDescriptionFile Field 2210 identifies the location of the service description file and ServiceName Field 2211 holds the logical name for the Internet service defined in the corresponding service description file. As in the other editing screens, all fields for the database as shown above the field columns, although not all fields may be displayed at one time.

As will be apparent to one skilled in the art, the fields depicted in these exemplary databases are not intended to limit the invention to the specific embodiment shown in the figures. Other fields may be added, depending on the types of services and equipment that is available and not all fields need to be present, depending on the complexity and requirements of the scheduling system.



### Illustrative Example

Various aspects of the invention will now be given with reference to an example, which shows other embodiments of various aspects of the invention.

Figures 23a and 23b show two embodiments of GUI 2300 used to perform scheduling tasks. GUI 2300 is comprised of Time Columns 2310 (which in the example is shown as Time Columns 2310a-2310d) and Channel Rows 2300 (which example rows are shown as Channel Rows 2320a-2320c). In Figure 23, Time Columns 2310a-2310d show information pertaining to time slots from 7:00pm to 8:30pm, in half-hour increments. Channel Rows 2320a-2320c show the schedule for television channel 52, pay-per-view channel 75, and cable channel 90, respectively. Also shown are Cells 2330a-2330c, which refer to Primary Events 2340a-2340c - "Friends," "Star Trek IV," and "Boxing," respectively. The different embodiments show that the service type may be displayed in a number of different ways, for instance, it may be identified with the service name, such as "TV:52", in Figure 23a or with the program, such as "TV:Friends" in Figure 23b.

In contrast to Figure 6, Figures 23a and 23b illustrate the use of varying the cell size in proportion to the duration of the event. Thus, "Friends" is scheduled for one hour and this is indicated by having Cell 2330a extend from 7:30pm to 8:00pm, or one half-hour cell. Likewise, "Star Trek IV" is scheduled for one and one-half hours and this is indicated by having Cell 2330b extend from 7:00pm to 8:30pm or three half-hour cells. In the same way Cell 2330c is two half-hour cells to represent a show duration of one hour.

Referring now to Figure 24a, there is shown Menu 2410 which is displayed upon, for instance, clicking the right button on a mouse when selecting Cell 2330a. A right pointing triangle shows that the Primary Event 2340a has supporting events and to indicate the hierarchical relationship between events. Menu 2410 shows two supporting events, Supporting Events 2410a and 2410b, which were added by the programmer to associate additional multimedia information with Primary Event 2340a. Supporting Event 2410a indicates that a data carousel will make the data in the file "Text\_Captions" available to a viewer during the scheduled timeframe. The data from the Text\_Captions is from a data carousel. Similarly, Supporting Event 2410b indicates that the IPPA (Internet Push Pull Agent) will make Internet information accessible to a viewer during the scheduled time. Of note is that only these two types of events may be selected associated with this type of primary event. Other types of primary events may have the ability to have other supporting

event types associated with it for a particular service. Such association is at the discretion of the programmer when creating a service. Figure 24b shows another embodiment where the supporting events are displayed directly underneath the event which it supports in a hierarchical fashion, in this case Primary Event 2340a. Figures 24c-24f show alternative embodiments which may be used to convey the relationships between a primary event and its supporting events.

Referring now to Figure 25, there is shown the Scheduler Data Model 2500 which show one embodiment which consolidates the primary events and supporting events shown in Figures 23a, 23b, 24a and 24b. As will be apparent to one skilled in the art, a single data model does not have to be used and relational data models may be used, for instance, which will simply distribute the information across different data models. Specifically, Scheduler Data Model 2500 is composed of a number of Records 2500, exemplary records numbered as Records 2510a-2510e. Each record is comprised of Fields 2520, individually identified as Fields 2520a-2520g. Of course, it will be apparent to one skilled in the art that these are only exemplary fields, and that additional fields may be added if desired for additional functionality.

Field 2510a holds the eventID, which is a unique identifier for each event. Field 2520b holds the programID, which is a unique identifier for each program and services to identify which events are related to a program. In the example, a particular episode of "Friends", Primary Event 2330a, is assigned a program ID of "1". Accordingly, Supporting Events 2410b and 2410c (eventID = 2 and 3) for Primary Event 2330a (eventID = 1), are also assigned a programID of 1. Field 2520c holds the channel that the primary event and its supporting events are being broadcast on. Hereinafter, eventID = x will be referred to as Event x.

Fields 2520e and 2520f hold the start and end time for each event. Although it is shown here that Events 1-3 are available from 7:30pm to 8:00pm, it is not necessary that all events for a program have the same time slot. For instance, Supporting Event 2410b (Friends\_Facts) may have a time from 7:30pm to 7:45pm. This allows a viewer to access such information only during the latter half of the show.

Field 2520g contains data referring to the service type. The service type provides more detailed information as to the media that the event is provided on. For instance, Event 1 is of type "TV" indicating that it is a regular television broadcast feed.

Event 2 is of type "DC" indicating that the information is from a data carousel. Event 3 is of type "IPPA" indicating that the information is from the Internet. In like fashion, Event 4 (Star Trek IV) is of type NVOD, indicating that it is a pay-per-view movie stored on a NVOD media server and Event 5 (Boxing) is of type TV, which is a television broadcast feed.

5           Reference is now made for Figures 26 and 27 showing portions of Data Models 2600 and 2700 for a data carousel and IPPA media server, respectively. In particular, DC Data Model 2600 is comprised of records 2610. Each record includes Field 2620a to 2620e. Fields 2620a contains the eventID for the supporting service, in this example, Event 2, Field 2620b holds the name and location of the file which contains the supporting text.  
10   Field 2620c holds that file's size for use by the system to allocate the resources it may need. Field 2620d holds the process identifier ("PID"), which is the identifier associated with that data so that other devices downstream of the data, such as a STB, can recognize and extract the data from a data stream.

          IPPA Data Model 2700 is also comprised of records 2710 and each record has  
15   Fields 2720a to 2720c. Field 2720a is the eventID for this supporting event, in this case Event 3. Field 2720b contains the URL where the Internet related information may be found. In the preferred embodiment, this may take the form of a URL (Uniform Resource Locator) from an internal or external Web page or even a data file which specifies a combination of Web pages in a manner similar to HTML frames. Field 2720c holds the PID for this data so  
20   that other devices downstream of the data, such as a STB, can recognize and extract the data from a data stream.

          Figure 28 shows an exemplary NVOD Data Model 2800. This embodiment shows the eventID (Field 2820a), location of the video (Field 2820b), size (Field 2820c), the process identifier (Field 2820d, and the transponder id (Field 2820e).

25           Data Models 2500, 2600, 2700 and 2800 are only illustrative examples of one embodiment of data models. Other embodiments will be apparent to those skilled in the art and these specified data models are presented for illustration purposes and are not intended to limit the scope of the invention in any way. Moreover, it is apparent to one skilled in the art that the population of these data models can be accomplished using table manipulation  
30   routines, samples of which are provided in Table 1.

          Once the schedule has been created, if the programmer then decides to commit to the schedule, Data Models 2500, 2600, 2700 and 2800, data models are populated from the

GUI using the table manipulation routines, such as those shown in Table 1. Alternatively, each entry in the data model is committed as soon as the programmer creates the entry in the GUI and the table manipulation routines are used to populate the appropriate data models as the schedule is created. As indicated, each data model may have its own set of specific table manipulation routines specific to the particular field structure of the data model. Primary events are also registered in Event Publish and Subscribe 420.

When the schedule shown in Figure 23 has been committed, or alternatively, during the committing of each schedule item, the exemplary system will also populate the tables used by Event Publish and Subscribe 420. Figures 29 and 30 depict one embodiment of such tables. In particular, Figure 29 shows Event Registration Table 2900. The table stores the primary event identifier in Field 2920a and the action of interest to its supporting events. In this example, Field 2920b stores the Change Type, which for Event 1 is of type ChangeTime, indicating that Event 1 would trigger other actions upon it changing to a different time slot. Other Change Types may of course be defined and used as needed, such as ChangeChannel, if the channel of an event will be modified, and so on. Figure 30 depicts Interest Registration Table 3000 which is used to register routines for events that would be interested when an event in Registration Table 2900 changes. Typically, the event in Registration Table 3000 would be the associated supporting events. Interest Registration Table 3000 stores in Field 3020a the primary or triggering event from Registration Table 2900. Field 3020b stores the ChangeType and Field 3020c stores the table manipulation routine calls that will be used to effect the change for the desired events.

The following exemplary table manipulation routines are used to manipulate Event Registration Table 2900 and Interest Registration Table 3000:

- Tmr\_RegisterEvent(eventID, changeType)
- Tmr\_RegisterInterest(eventID, changeType, changeParameters)

The following routine is used to change the event time for the identified event:

- Tmr\_ChangeEventTime(eventID, newTime, endTime)

The following event is used to inform other data models and tables of the change:

- Tmr\_PostEventChange(psEvent, eventID, changePartners)

Figures 25 29, 30 and 31 will now be used to illustrate one embodiment of Event Publish and Subscribe 420. When Event 1 (Record 2510a) shown on Figure 25 is committed, the table manipulation routine below is called to register Event 1 in event Registration Table 2900.

Tmr\_RegisterEvent(1, ChangeTime)

Record 2910a shows the result of the call.

Since this is a television service type, the example defines the use of two supporting types for the sake of illustration. Of course, other supporting types can be used to create a more full featured service. Once the primary event has been registered, the supporting events of interest must be registered. To register, Event Publish and Subscribe 420 calls the routines:

Tmr\_RegisterInterest(1, ChangeTime, [Tmr\_ChangeEventTime, 2 <newtime>]) and

Tmr\_RegisterInterest(1, ChangeTime, [Tmr\_ChangeEventTime, 3 <newtime>]).

Note that the parameter changeParameter of Tmr\_RegisterInterest is a parameter list which will vary depending on what is required of the routine begin registered. In this example, the routine Tmr\_ChangeEventTime has two parameters, eventID and newTime. The parameter "<newTime>" indicates that the parameter will be filled in by the appropriate time when this routine is called. Furthermore, in this example, the Tmr\_ChangeEventTime routine is flexible enough to handle the time change in both the data carousel and IPPA data models. If there was a separate routine for each data model, then the routine calls may take the form:

Tmr\_RegisterInterest(1, ChangeTime, [Tmr\_DCChangeEventTime, 2, <newtime>]) and

Tmr\_RegisterInterest(1, ChangeTime, [Tmr\_IPPACheckChangeEventTime, 3 <newtime>]).

The result of calling the Tmr\_RegisterInterest routines is shown in Figure 30 where the Tmr\_ChangeEventTime routines are registered to take effect when a time change to Event 1 occurs. This completes the registration procedures in this example.

Continuing with the example, if the programmer later decides to change Friends from the 7:30 time slot to 9:00, then the following sequence of events will transpire in this embodiment. First, Event Publish and Subscribe 420 will change the time for the primary event. This is accomplished by calling

Tmr\_ChangeEventTime(1, 9:00pm).

Note that in the preferred embodiment an end time does not have to be specified. In one embodiment, the end time is specified. In another embodiment, the duration of the show is specified. If only the newTime is specified, Event Publish and Subscribe 420 will assume that the program will have the same length of time as originally scheduled. The result of this call is to update Data Model 2500 as shown in Record 2510a in Figure 31.

Next Even Publish and Subscribe 420 inspects Event Registration Table 2900 for any dependencies on Event 1. Since Event 1 is registered, dependencies are implied. Also, since Event 1 changed its time, the change would apply to the dependency in this case. Event Publish and Subscribe 420 then calls the routine

Tmr\_PostEventChange(1, ChangeTime, 9:00pm)

which will begin the process to execute any registered procedures with events supporting Event 1 for a time change to 9:00pm.

The Tmr\_PostEventChange call operates by scanning Interest Registration Table 3000 for all routines associated with Even 1 and of ChangeType ChangeTime. Here, Records 3010a and 3010b were identified. Event Publish and Subscribe 420 then makes the following calls based on the data stored in Field 3020c:

Tmr\_ChangeEventTime, 2, 9:00pm) and

Tmr\_ChangeEventTime, 3, 9:00pm).

This causes changes to the appropriate data models, which in this example would be Data Model 2500, the results shown in Records 2510b and 2510c in Figure 31. Even Publish and Subscribe 420 will then determine if there are dependencies on Events 2 and 3 and execute any registered routines for them. In the instant case there are none and the publish and subscribe mechanism completes propagating any further changes.

After the schedule is complete, the operator may choose to create and distribute the tasks based on the schedule. Task Distributor 410 is responsible for creating the tasks. Using Schedule 2500 as shown in Figure 31 for illustration, Task Distribute 410 creates a number of tasks. In the preferred embodiment these tasks are four-tuples with the form [taskId, assestList, operator, time, data]. With respect to Records 2510b and 2510c, Task Distributor 410 creates the following two tasks:

- [TaskID 1, "Text\_Captions", "Play", [9:00pm, 9:30pm], [90037, 3]]
- [TaskID 2, "Friends\_Facts", "Play", [9:00pm, 9:30pm], [80716]]

In this example, the "Play" operator indicates to the media server that it should begin playing/transmitting the requested data at the specified time. As will be known to those skilled in the art, other operators may be available, depending on the media server and functionality desired.

5           The tasks are then placed in Thread Pool and Queue 430 which tracks and controls the distribution of the tasks and receipt of status messages. At the appropriate time or command, Thread and Pool Queue 430 distributes the task to the appropriate media server through Master/Slave Scheduler API 180a. In this example, TaskID 1 is distributed to the data carousel and TaskID 2 is distributed to the IPPA. In addition, Thread Pool and Queue  
10   430 logs the distributed tasks to track the status of those tasks.

          TaskID 1 and 2 are received by the data carousel and IPPA media servers' respective Timeline and Task Management 510 units. The Timeline and Task Management Unit 510 tracks the tasks received for the media server and controls the execution of a task on the media server.

15           Figure 32a shows one embodiment of a queue, Queue 3200, maintained by Time and Task Management Unit 510 for the data carousel. In particular, Time and Task Management Unit 510 stores in Queue 3200 information needed by the media server to deliver the requested asset. For instance, Queue 3200 may contain the date in Field 3210 and the start and stop time that the asset, identified in Asset List 3210g, should be delivered in  
20   Fields 3210b and 3210c. The start time in Field 3210b has been adjusted to account for the delta variance of three (3) seconds for this exemplary media server. TaskID is a unique task identifier. In this example, the TaskID is the Concentration of a Master Scheduler ID (assumed to be "1") and the EventID. Other ways of obtaining a unique TaskID are known to those skilled in the art. Fields 3210e and 3210f contains the command and associated  
25   command data to be executed Task Translation 520.

          Figure 32b illustrates another embodiment similar to that shown in Figure 32a, but with the start time (Field 3210b) unadjusted, but with an additional field, Field 3210h, which holds the time the task is to be executed after adjusting for the delta variance.

          Figures 33a and 33b shows Queue 3300 for the IPPA media server and fields  
30   similar to that shown in Figure 32a and 32b. As will be apparent to one skilled in the art, the delta variance may have been provided by Master Scheduler 120, as in Figure 3200, or may

be known by the media server itself, as in Figure 3300, or other such embodiments. and the delta variance may be different for different media server commands.

Moreover, other embodiments of Queue 3300 may indicate the delta variance to be used, although in the preferred embodiment, the media server has a single preset delta variance. One such embodiment may be for the media server to know the delta variance, but nevertheless store it in a queue such as shown in Figures 32a and 32b to simplify processing at the appropriate time.

In the preferred embodiments, all tuples received from the Master Scheduler are stored in the queue and the queues are stored sorted by time, thus the system can easily determine the next task to execute by simply examining the top of the queue.

At the indicated time the task (the tuple, unadjusted or otherwise adjusted with a delta variance), is removed from the queue, such as the queues shown in Figures 32a, 32b, 33a and 33b, and passed to Task Translation 520. Task Translation 520 translates the requested task into one or more media server specific tasks. The "Play" task sent by the Master Scheduler may, for instance, be translated into a number of tasks for a data carousel, such as DC\_Initialize\_Slot, DC\_Load\_Slot, DC\_Transmit\_Slot\_Data. In the preferred embodiment as FSM is spawned to track these tasks and report back to Master Scheduler 120 the status of the "Play" task. Figure 34 shows an example of a high-level FSM 3400 for the Play task. Specifically, FSM 3400 enters ttLoaded State 3410 and proceeds to ttExecute State 3420. If all the media specific tasks executed correctly, then FSM 3400 proceeds to ttComplete State 3440, otherwise FMS 3400 proceeds to ttError state 3430.

Block 3450 shows that ttExecute State 3420 translates into a number of device specific API calls (and other code, if desired) corresponding to a data carousel "Play" command. At the conclusion of each device specific API call, FSM 3400 either proceeds to the next task or goes to ttError State 3430 for reporting the error back to Master Scheduler 120. Each device specific API call will then, through Device Specific API 190a, control the appropriate bit-pump.

In the manner described above, the present invention thus provides a system and method to associate and control multimedia events with a primary event and to provide a system and method for a distributed multimedia scheduling system. While this invention has been described with reference to the preferred embodiments, other modifications will become apparent to those skilled in the art by study of the specification and drawings. It is thus



intended that the following appended claims include such modifications as fall within the spirit and scope of the present invention.

## CLAIMS

## WHAT IS CLAIMED IS:

1. A method for controlling a media server to output data at a predetermined time comprising:

5           inputting a program schedule into a master scheduler wherein said program schedule comprises event information;

          processing said program schedule to create a task from said program schedule wherein said master scheduler performs said processing said program schedule;

          distributing said task to a slave task scheduler;

10           processing said task to create a command suitable for a media server wherein said slave task scheduler performs said processing said task;

          sending said command to said media server to retrieve data from said media server;

          retrieving data from said media server in accordance with said command;

15           outputting said retrieved data.

2. A method according to Claim 1 wherein said media server is adapted to operate independently of said master scheduler so that said media server may continue to execute said tasks irrespective of whether said master scheduler is available at said  
20   predetermined time.

3. A method for controlling a media server to output data at a predetermined time comprising:

25           creating a schedule for a service wherein said schedule is comprised of schedule data;

          storing said schedule data in a data model wherein said data model is adapted for a service;

          processing said data to create a task;

          distributing said task to a slave task scheduler;

30           processing said task and sending a command to a media server at a predetermined time.

4. A method for scheduling multimedia programs comprising:  
creating a primary event in a schedule wherein said creating uses a graphical  
user interface; selecting a multimedia event to associate with said primary event wherein said  
selecting uses said graphical user interface;

5 associating said multimedia event with said primary event in said schedule  
wherein said associating uses said graphical user interface;

transforming said schedule into at least one task wherein said transforming  
creates a task for a media server to provide said associated multimedia event;

distributing said task to said media server;

10 executing said task at a predetermined time.

5. A method according to Claim 4 wherein said graphical user interface uses a  
grid layout for scheduling.

15 6. A method according to Claim 5 wherein said selecting a multimedia event  
using a graphical user interface presents a user a menu of choices.

7. A method according to Claim 5 wherein said creating of said primary event  
and said associating said multimedia event with said primary event uses a cell in said grid in  
20 said graphical user interface.

8. A method for scheduling multimedia events comprising:  
creating a primary event in a schedule;  
associating a supporting event with said primary event in said schedule;  
25 processing said schedule and creating at least one task from said supporting  
event; distributing said task to a media server wherein said media server accesses multimedia  
corresponding to said supporting event;

processing said task and initiating at a predetermined time said media server to  
access and distribute said multimedia.

30 9. A method according to Claim 8 wherein said primary event and said  
supporting event are associated with a cell in said schedule.

10. A method according to Claim 8 wherein said associating said primary event and said supporting event creates a graph wherein said primary event is a node and said secondary event is a leaf on a graph.

5 11. A method according Claim 8 wherein said predetermined time includes a delta variance.

10 12. A method for scheduling related events comprising:  
creating a primary event in a schedule;  
associating a supporting event with said primary event wherein said supporting event is a multimedia event that will be distributed at a predetermined time and does not use cue tones;  
15 translating said supporting event into at least one task by a master scheduler;  
distributing said task to a media server;  
translating said task into at least one device specific command for a bit-pump at a predetermined time;  
20 sending said device specific command to said bit-pump;  
processing said device specific command by said bit-pump and distributing requested data corresponding to said supporting event.

25 13. A method according to Claim 12 wherein said media server is independent of the availability of said master scheduler when a task has been distributed to said media server wherein said task will execute at a predetermined time even if said master scheduler has become unavailable.

14. A method according to Claims 2 or 13 wherein a status signal is sent to the master scheduler upon the completion of said execution of said task.

30 15. A system for controlling a media server to output data at a predetermined time comprising:

input means for inputting a program schedule into a master scheduler wherein said program schedule comprises event information;

first processing means for processing said program schedule to create a task from said program schedule wherein said master scheduler performs said processing said

5 program schedule;

distribution means for distributing said task to a slave task scheduler;

second processing means for processing said task to create a command suitable for a media server wherein said slave task scheduler performs said processing said task;

10 sending means for sending said command to said media server to retrieve data from said media server;

retrieving means for retrieving data from said media server in accordance with said command;

output means for outputting said retrieved data.

15

16. A system for controlling a media server to output data at a predetermined time comprising:

creating means for creating a schedule for a service wherein said schedule is comprised of schedule data;

20

storage means for storing said schedule data in a data model wherein said data model is adapted for a service;

first processing means for processing said data to create a task;

distribution means for distributing said task to a slave task scheduler;

second processing means for processing said task and sending a command to a media server

25

at a predetermined time.

17. A system for scheduling multimedia programs comprising:

creating means for creating a primary event in a schedule wherein said creating uses a graphical user interface;

30

selecting means for selecting a multimedia event to associate with said primary event wherein said selecting uses said graphical user interface;

associating means for associating said multimedia event with said primary event in said schedule wherein said associating uses said graphical user interface;

transforming means for transforming said schedule into at least one task wherein said transforming creates a task for a media server to provide said associated multimedia event;

distribution means for distributing said task to said media server;

executing means for executing said task at a predetermined time.

18. A system for scheduling multimedia events comprising:

a graphical user interface for scheduling primary and supporting events; a master scheduler wherein said master scheduler generates tasks from said schedule;

a media server;

a distributor module wherein said distributor distributes said tasks to said

media server;

said media server comprising a bit pump;

a timeline and task management module wherein said time and task management module receives said task from said distributor module;

a task translation module to receive said task, translate said tasks into commands and send said commands to said bit pump.

19. A method for synchronizing and propagating changes to an event comprising:

assigning an event an event identifier;

registering an event in a first table wherein said first table stores the event identifier and an event trigger;

registering interests in a second table wherein said second table stores a procedure to execute for said event trigger;

changing said event wherein said change generates an event trigger;

inspecting said first table for said event trigger for said event;

inspecting said second table for said procedure to execute upon said event trigger event for said event identifier;

executing said procedure.

20. A method according to claim 19 wherein said inspecting of said first table uses said event identifier.

5

21. A method according to claim 19 wherein said inspecting of said second table uses said event identifier and said event trigger.

10

22. A method according to claim 19 wherein said procedure modifies a data model.

23. A system for synchronizing and propagating changes to an event comprising:

15

assigning means for assigning an event an event identifier;

first registering means for registering an event in a first table wherein said first table stores the event identifier and an event trigger;

second registering means for registering interests in a second table wherein said second table stores a procedure to execute for said event trigger;

20

changing means for changing said event wherein said change generates an event trigger;

first inspecting means for inspecting said first table for said event trigger for said event;

second inspecting means for inspecting said second table for said procedure to execute upon said event trigger event for said event identifier;

25

executing means for executing said procedure.

24. A system according to claim 19 wherein said first inspecting means uses said event identifier.

30

25. A system according to claim 19 wherein said second inspecting means uses said event identifier and said event trigger.

26. A system according to claim 19 wherein execution of said procedure modifies a data model.

27. A computer program embodied on a computer-readable medium for  
5 synchronizing and propagating changes to an event comprising:  
    assigning code segment for assigning an event an event identifier;  
    first registering code segment for registering an event in a first table wherein  
said first table stores the event identifier and an event trigger second registering code segment  
for registering interests in a second table wherein said second table stores a procedure to  
10 execute for said event trigger;  
    changing code segment for changing said event wherein said change generates  
an event trigger;  
    first inspecting code segment for inspecting said first table for said event  
trigger for said event;  
15 second inspecting code segment for inspecting said second table for said  
procedure to execute upon said event trigger event for said event identifier;  
    executing code segment for executing said procedure.

28. A computer program embodied on a computer-readable medium for  
20 controlling a media server to output data at a predetermined time comprising:  
    input code segment for inputting a program schedule into a master scheduler  
wherein said program schedule comprises event information;  
    first processing code segment for processing said program schedule to create a  
task from said program schedule wherein said master scheduler performs said processing said  
25 program schedule;  
    distribution code segment for distributing said task to a slave task scheduler;  
    second processing code segment for processing said task to create a command  
suitable for a media server wherein said slave task scheduler performs said processing said  
task;  
30 sending code segment for sending said command to said media server to  
retrieve data from said media server;



retrieving code segment for retrieving data from said media server in  
accordance with said command;  
output code segment for outputting said retrieved data.

5           29. A computer program embodied on computer-readable medium for  
controlling a media server to output data at a predetermined time comprising:  
          schedule creation code segment for creating a schedule for a service wherein  
          said schedule is comprised of schedule data;  
          storage code segment for storing said schedule data in a data model wherein  
10   said data model is adapted for a service;  
          first processing code segment for processing said data to create a task;  
          distribution code segment for distributing said task to a slave task scheduler;  
          second processing code segment for processing said task and sending a  
          command to a media server at a predetermined time.

15           30. A computer program embodied on a computer-readable medium for  
scheduling multimedia programs comprising:  
          event creation code segment for creating a primary event in a schedule  
          wherein said creating uses a graphical user interface;  
20           selection code segment for selecting a multimedia event to associate with said  
primary event wherein said selecting uses said graphical user interface;  
          association code segment for associating said multimedia event with said  
primary event in said schedule wherein said associating uses said graphical user interface;  
          transforming code segment for transforming said schedule into at least one  
25   task wherein said transforming creates a task for a media server to provide said associated  
multimedia event;  
          distribution code segment for distributing said task to said media server;  
          execution code segment for executing said task at a predetermined time.

30           31. A computer program embodied on a computer-readable medium for  
scheduling multimedia events comprising:  
          creation code segment for creating a primary event in a schedule;

association code segment for associating a supporting event with said primary event in said schedule;

first processing code segment for processing said schedule and creating at least one task from said supporting event;

5 distribution code segment for distributing said task to a media server wherein said media server accesses multimedia corresponding to said supporting event;

first processing code segment for processing said task and initiating at a predetermined time said media server to access and distribute said multimedia.

10 32. A computer program embodied on a computer-readable medium for scheduling related events comprising:

creating code segment for creating a primary event in a schedule;

associating code segment for associating a supporting event with said primary event wherein said supporting event is a multimedia event that will be distributed at a  
15 predetermined time and does not use cue tones;

first translation code segment for translating said supporting event into at least one task by a master scheduler;

distribution code segment for distributing said task to a media server;

20 second translation code segment for translating said task into at least one device specific command for a bit-pump at a predetermined time;

sending code segment for sending said device specific command to said bit-pump;

processing code segment for processing said device specific command by said bit-pump and distributing requested data corresponding to said supporting event.

FIG. 1




FIG. 2




FIG. 3a




FIG. 3b




FIG. 3c




FIG. 4a






FIG. 4b




FIG. 5




FIG. 6




FIG. 7

700

**Select a Date and Time**

Year ..... 1997

Month ..... August

Day ..... 26th

Hour ..... 12:00 PM

Cancel Done

FIG. 8




FIG. 9

622c




FIG. 10

Program Services Master Scheduler XI				
File Edit View Select				
DATE: August 26th, 1997 TIME: 12:00 to 01:00 SERVICE: KABC EVENT: ESPY.MPG				
	12:00 PM	1:00 PM	2:00 PM	3:00 PM
HOME				
MSB-101		MSB   config1.dat		
MSB-102		MSB   config2.dat		
INET-101			INET   c:\ppa\per	
INET-102				
KABC		TV   ESPY		
KCBS				
KTVU				
KNBC				
COURT				
CNN				
TBS				

622d

1001

FIG. 11






FIG. 12




FIG. 13

**Program Services Master Scheduler**

File Edit View Select

SATUR August 26th, 1997 TIME 12:00 to 01:00 service KABC from sworts.2mt

INET | c:\ippa\per

▼ TV | ESPY

▼ GDC | sworts.2mt

Start Date: 1997-08-26

Start Time: 12:00

Stop Date: 1997-08-26

Stop Time: 01:00

Cancel Date

1101

1302

1303

1304

1305

1301

INET-101

INET-102

KABC

KCBS

KTVU

KNBC

COURT

CNN

TBS

BET

DCH

SHO

HBO

FIG. 14




FIG. 15

1501

610c

**File** **Edit** **View** **Select** **Program Services Master Scheduler** **XL**

Aug 26th, 1991 MSB-101 2:00 PM 3:00 PM

1: GDC Database...

MSB Database...

INET Database...

M DVB Services...

Display Times...

Hide Times...

T Refresh Ctrl+R

HOME			
MSB-101			
MSB-102			
INET-101			
INET-102			
KABC			
KCBS			
KTVU			
KNBC			
COURT			
CNN			
TBS			

INET |c:\apps\peer



FIG. 17

622c

1601a

1601

**Program Services Master Scheduler**

File Edit View Select EPG Database... MSB-101 exam config1.dat

August 26th, 1998

1. GDC Database...

2. MSB Database...

3. INET Database...

4. DVB Services...

Display Times...

Hide Times...

T Refresh Ctrl+R

Channel	Time	Program
HOME		
MSB-101		
MSB-102		
INET-101		
INET-102		
KABC		
KCBS		
KTVU		
KNBC		
COURT		
CNN		
TBS		

02:30 MSB | config1.dat

INET | c:\lppa\acc

2:00 PM 3:00 PM

FIG. 18

[illegible]





FIG. 20

GDC Database				
Select	Insert	Update	Delete	Clear
AssetURL	ProgramID	Speed	Bandwidth	Question
/americast/code/input/sworfas.m2t	201	1	5300000	P
/americast/code/input/ESPY.MPG	401	1	5300000	P
ESPY.MPG	402	1	10	D
sworfas.2mt	403	1	10	D
ESPY.MPG	404	1	10	D
sworfas.2mt	405	1	10	D
ESPY.MPG	406	1	10	D
sworfas.2mt	407	1	10	D
ESPY.MPG	1004	100	10	P
ESPY.MPG	1008	100	10	P
ESPY.MPG	1032	100	10	P
dummy.xyp	1034	100	10	P
sworfas.2mt	1036	100	10	P
ESPY.MPG	1056	100	10	P

2010

1911

2011

2012

2013

FIG. 21

**MSB Database**

**Programs** | **Events** | **Types** | **Select** | **Clear** | **Insert** | **Update** | **Delete**

ProgramID: 1010 Start Date: 1997-08-26 Start Time: 12:00:00

ContainerID: 102 End Date: 1997-08-26 End Time: 01:00:00

ProgramID	ContainerID	Start Date	Start Time	Stop Date	Stop Time
100	102	1997-09-05	23:59:00	1997-09-05	23:59:30
200	103	1997-09-05	23:59:00	1997-09-05	23:59:30
1010	102	1997-08-26	12:00:00	1997-08-26	01:00:00
1018	102	1997-08-26	12:00:00	1997-08-26	01:00:00
1020	102	1997-08-26	12:00:00	1997-08-26	01:00:00
1022	102	1997-08-26	12:00:00	1997-08-26	01:00:00
1024	102	1997-08-26	12:00:00	1997-08-26	01:00:00
1026	102	1997-08-26	12:00:00	1997-08-26	01:00:00
1028	102	1997-08-26	12:00:00	1997-08-26	01:00:00
1038	102	1997-08-26	12:00:00	1997-08-26	01:00:00
1040	102	1997-08-26	12:00:00	1997-08-26	01:00:00

1911 2110 2111 2112 2113 2114

FIG. 22

**INET Database**

XI

Select
Clear
Insert
Update
Delete

Descrpt File.....  
 c:\ippa\services\weather.sdf

ProgramID...  
 1001

ServiceID.....  
 20

Start Date....  
 1997-09-08

Start Time....  
 18:06:30

Service Name.....  
 WeatherService

End Date.....  
 1997-09-08

End Time.....  
 22:30:00

ServiceID	Service Name	ProgramID	ServiceID	Service Name
c:\ippa\services\stock.sdf	StockService1	1000	10	WeatherService1
c:\ippa\services\weather.sdf	Traffic	1001	20	Service Description File
c:\ippa\services\traffic.sdf	Weather IPPA	1002	30	Weather IPPA
c:\ippa\services\stock.sdf	Weather IPPA	1006	0	Weather IPPA
c:\ippa\services\traffic.sdf	Weather IPPA	1012	0	Stock IPPA
c:\ippa\services\weather.sdf		1014	0	
c:\ippa\services\stock.sdf		1016	0	
c:\ippa\services\stock.sdf		1030	0	

2210
1911
1810
2211

FIG. 23a

Service		2340b	2330b	2340a	2330a	2330c	2300
2320a	TV: 52						
	2320b						
	PPV: 75						
	2320c						
2320	TV: 90						
2340c							

2320a

2320b

2320c

2320

2340c

2340b

2330b

2340a

2330a

2330c

2300

2330

7:00pm

7:30pm

8:00pm

8:30pm

Friends

Star Trek IV

Boxing

2310a

2310b

2310c

2310d

2310

FIG. 23b

Service		2340b	2330b	2340a	2330a	2330c	2300
2320a	Channel 52				7:30pm	8:00pm	
	Channel 75				TV: Friends		
	Channel 90				TV: Boxing		
2320c							
2340c							
2320							
2310a							
2310b							
2310c							
2310d							

**FIG. 24a**

[illegible]

**FIG. 24b**

[illegible]

FIG. 24c




FIG. 24d






FIG. 24e




FIG. 24f




FIG. 25

2510

2510a eventID	2510b programID	2510c Channel	2510d Event Name	2510e Start Time	2510f End Time	2510g Service Type
1	1	52	Friends	7:30pm	8:00pm	TV
2	1	52	Friends Text_Captions	7:30pm	8:00pm	DC
3	1	52	Friends Friends_Facts	7:30pm	8:00pm	IPPA
4	5	75	Star Trek IV	7:00pm	8:30pm	NVOD
5	7	90	Boxing	7:00pm	8:30pm	TV

2500

FIG. 26

2610	2620a	2620b	2620c	2620d	2620e	2620
	eventID	Filename	Size	PID	Transponder	
2610a	2	Text_Captions.txt	50K	90037	3	

2600

FIG. 27

2710	2720a	2720b	2720c	2720	2700
	eventID	URL	PID		
2710a	3	Friends_Facts.sdf	80716		

FIG. 28

2810

2610a

2820a

2820b

2820c

2820d

2820e

2820

eventID	Filename	Size	PID	Transponder
4	Star Trek IV	500 Meg	90020	10

2800

FIG. 29

2920	
2920a	2920b
eventID	ChangeType
1	ChangeTime

2910

2910a

2900

FIG. 30

3000		
3020a	3020b	3020c
eventID	ChangeType	Registered Procedure
1	ChangeTime	Tmr_ChangeEventTime(2, <newTime>)
1	ChangeTime	Tmr_ChangeEventTime(3, <newTime>)

3010

3010a

3010b

FIG. 31

2510	2520a	2520b	2520c	2520d	2520e	2520f	2520g
	eventID	programID	Channel	Event Name	Start Time	End Time	Service Type
2510a	1	1	52	Friends	9:00pm	9:30pm	TV
2510b	2	1	52	Text_Captions	9:00pm	9:30pm	DC
2510c	3	1	52	Friends_Facts	9:00pm	9:30pm	IPPA
2510d	4	5	75	Star Trek IV	7:00pm	8:30pm	NVOD
2510e	5	7	90	Boxing	7:00pm	8:30pm	TV

2500

FIG. 32a

3210a	3210b	3210c	3210d	3210e	3210f	3210g
Date	Start Time	End Time	TaskID	Command	Cmd Data	Asset List
1997-08-01	8:59:57pm	9:30pm	1:2	Play		Text_Captions.txt

3200

FIG. 32b

3210a	3210b	3210c	3210d	3210e	3210f	3210g
Date	Start Time	Exec Time	End Time	TaskID	Command	Asset List
1997-08-01	9:00pm	8:59:57pm	9:30pm	1:2	Play	Text_Captions.txt

3201

FIG. 33a

3210a	3210b	3210c	3210d	3210e	3210f	3210g
Date	Start Time	End Time	TaskID	Command	Cmd Data	Asset List
1997-08-01	8:59:57pm	9:30pm	1:3	Play		Friends_Facts.sdf

3300


FIG. 33b

3210a	3210b	3210h	3210c	3210d	3210e	3210f	3210g
Date	Start Time	Exec Time	End Time	TaskID	Command	Cmd Data	Asset List
1997-08-01	9:00pm	8:59:57pm	9:30pm	1:3	Play		Friends_Facts.sdf

3301



FIG. 34



## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US99/19028

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : G06F 15/00

US CL : 345/327; 709/217, 218, 219; 348/906

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 345/327; 709/217, 218, 219; 348/906, 722, 7, 9

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,659,350 A (HENDRICKS et al) 19 August 1997, see whole document.	1-32
Y	US 5,583,937 A (ULLRICH et al) 10 December 1996, see whole document	1-32
A,E	US 6,008,803 A (ROWE et al) 28 December 1999, see whole document.	1-32
A,P	US 5,850,218 A (LAJOIE et al) 15 December 1998, see whole document.	1-32



Further documents are listed in the continuation of Box C.



See patent family annex.

*A*	document defining the general state of the art which is not considered to be of particular relevance	*T*	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*E*	earlier document published on or after the international filing date	*X*	document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*I*	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Y*	document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*O*	document referring to an oral disclosure, use, exhibition or other means	*A*	document member of the same patent family
*P*	document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

13 JANUARY 2000

Date of mailing of the international search report

10 FEB 2000

Name and address of the ISA/US

Patent Office, International Patent Center

1500 PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Name and address of the ISA/US

Patent Office, International Patent Center

1500 PCT  
Washington, D.C. 20231

Telephone No. (703) 305-0627

Form PCT/ISA/210 (second sheet)(July 1992)\*



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification <sup>7</sup> : <b>G06F 15/00</b>	<b>A1</b>	(11) International Publication Number: <b>WO 00/11561</b>
		(43) International Publication Date: 2 March 2000 (02.03.00)
(21) International Application Number: PCT/US99/19028		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 20 August 1999 (20.08.99)		
(30) Priority Data: 09/137,618 21 August 1998 (21.08.98) US		
(71) Applicant: CORPORATE MEDIA PARTNERS doing business as AMERICAST [US/US]; 5th Floor, 3601 W. Olive Avenue, Burbank, CA 91505 (US).		
(72) Inventor: SEQUEIRA, William, J.; 4248 Balfour Avenue, Oakland, CA 94610 (US).		
(74) Agent: OSTROW, Seth, H.; Brown Raysman Millstein Felder & Steiner, LLP, 120 West Forty-Fifth Street, New York, NY 10036 (US).		

**Published***With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: SYSTEM AND METHOD FOR A MASTER SCHEDULER

## (57) Abstract

A system and method for associating and controlling multimedia supporting events with a primary event. The events are translated into tasks and sent to media servers (130) for execution at a predetermined time by being further translated into media specific tasks to control a bit-pump (150).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		